

Inventory Control Form

Small Fragment Locking Compression Plate (LCP®) System

Case Information (eg, Case ID):

DO NOT PUT ANY
PATIENT IDENTIFIABLE
INFORMATION IN
THIS FIELD

To order (USA): 800-523-0322

To order (Canada): 855-946-8999

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

2.7 mm Cortex Screws, self-tapping



	Length		Length		
<input type="checkbox"/>	202.810	10 mm	<input type="checkbox"/>	202.830	30 mm
<input type="checkbox"/>	202.812	12 mm	<input type="checkbox"/>	202.832	32 mm
<input type="checkbox"/>	202.814	14 mm	<input type="checkbox"/>	202.834	34 mm
<input type="checkbox"/>	202.816	16 mm	<input type="checkbox"/>	202.836	36 mm
<input type="checkbox"/>	202.818	18 mm	<input type="checkbox"/>	202.838	38 mm
<input type="checkbox"/>	202.820	20 mm	<input type="checkbox"/>	202.840	40 mm
<input type="checkbox"/>	202.822	22 mm	<input type="checkbox"/>	202.845	45 mm
<input type="checkbox"/>	202.824	24 mm	<input type="checkbox"/>	202.850	50 mm
<input type="checkbox"/>	202.826	26 mm	<input type="checkbox"/>	202.855	55 mm
<input type="checkbox"/>	202.828	28 mm			

3.5 mm Cortex Screws, self-tapping



	Length		Length		
<input type="checkbox"/>	204.810	10 mm	<input type="checkbox"/>	204.834	34 mm
<input type="checkbox"/>	204.812	12 mm	<input type="checkbox"/>	204.836	36 mm
<input type="checkbox"/>	204.814	14 mm	<input type="checkbox"/>	204.838	38 mm
<input type="checkbox"/>	204.816	16 mm	<input type="checkbox"/>	204.840	40 mm
<input type="checkbox"/>	204.818	18 mm	<input type="checkbox"/>	204.842	42 mm
<input type="checkbox"/>	204.820	20 mm	<input type="checkbox"/>	204.844	44 mm
<input type="checkbox"/>	204.822	22 mm	<input type="checkbox"/>	204.845	45 mm
<input type="checkbox"/>	204.824	24 mm	<input type="checkbox"/>	204.846	46 mm
<input type="checkbox"/>	204.826	26 mm	<input type="checkbox"/>	204.848	48 mm
<input type="checkbox"/>	204.828	28 mm	<input type="checkbox"/>	204.850	50 mm
<input type="checkbox"/>	204.830	30 mm	<input type="checkbox"/>	204.855	55 mm
<input type="checkbox"/>	204.832	32 mm	<input type="checkbox"/>	204.860	60 mm

3.5 mm Locking Screws, self-tapping, with StarDrive™ Recess



	Length		Length		
<input type="checkbox"/>	02.212.054	54 mm	<input type="checkbox"/>	212.113	34 mm
<input type="checkbox"/>	02.212.056	56 mm	<input type="checkbox"/>	212.114	35 mm
<input type="checkbox"/>	02.212.058	58 mm	<input type="checkbox"/>	212.115	36 mm
<input type="checkbox"/>	212.101	10 mm	<input type="checkbox"/>	212.116	38 mm
<input type="checkbox"/>	212.102	12 mm	<input type="checkbox"/>	212.117	40 mm
<input type="checkbox"/>	212.103	14 mm	<input type="checkbox"/>	212.118	42 mm
<input type="checkbox"/>	212.104	16 mm	<input type="checkbox"/>	212.119	45 mm
<input type="checkbox"/>	212.105	18 mm	<input type="checkbox"/>	212.120	48 mm
<input type="checkbox"/>	212.106	20 mm	<input type="checkbox"/>	212.121	50 mm
<input type="checkbox"/>	212.107	22 mm	<input type="checkbox"/>	212.122	52 mm
<input type="checkbox"/>	212.108	24 mm	<input type="checkbox"/>	212.123	55 mm
<input type="checkbox"/>	212.109	26 mm	<input type="checkbox"/>	212.124	60 mm
<input type="checkbox"/>	212.110	28 mm	<input type="checkbox"/>	212.134	44 mm
<input type="checkbox"/>	212.111	30 mm	<input type="checkbox"/>	212.136	46 mm
<input type="checkbox"/>	212.112	32 mm			

3.5 mm Cortex Screws, self-tapping, with T15 StarDrive Recess



	Length		Length		
<input type="checkbox"/>	02.200.010	10 mm	<input type="checkbox"/>	02.200.034	34 mm
<input type="checkbox"/>	02.200.012	12 mm	<input type="checkbox"/>	02.200.036	36 mm
<input type="checkbox"/>	02.200.014	14 mm	<input type="checkbox"/>	02.200.038	38 mm
<input type="checkbox"/>	02.200.016	16 mm	<input type="checkbox"/>	02.200.040	40 mm
<input type="checkbox"/>	02.200.018	18 mm	<input type="checkbox"/>	02.200.042	42 mm
<input type="checkbox"/>	02.200.020	20 mm	<input type="checkbox"/>	02.200.044	44 mm
<input type="checkbox"/>	02.200.022	22 mm	<input type="checkbox"/>	02.200.045	45 mm
<input type="checkbox"/>	02.200.024	24 mm	<input type="checkbox"/>	02.200.046	46 mm
<input type="checkbox"/>	02.200.026	26 mm	<input type="checkbox"/>	02.200.048	48 mm
<input type="checkbox"/>	02.200.028	28 mm	<input type="checkbox"/>	02.200.050	50 mm
<input type="checkbox"/>	02.200.030	30 mm	<input type="checkbox"/>	02.200.055	55 mm
<input type="checkbox"/>	02.200.032	32 mm	<input type="checkbox"/>	02.200.060	60 mm

Inventory Control Form

Small Fragment Locking Compression Plate (LCP) System



PART OF THE *Johnson & Johnson* FAMILY OF COMPANIES

Implants (cont'd)

4.0 mm Cancellous Bone Screws, fully threaded



	Length		Length		
<input type="checkbox"/>	206.010	10 mm	<input type="checkbox"/>	206.028	28 mm
<input type="checkbox"/>	206.012	12 mm	<input type="checkbox"/>	206.030	30 mm
<input type="checkbox"/>	206.014	14 mm	<input type="checkbox"/>	206.035	35 mm
<input type="checkbox"/>	206.016	16 mm	<input type="checkbox"/>	206.040	40 mm
<input type="checkbox"/>	206.018	18 mm	<input type="checkbox"/>	206.045	45 mm
<input type="checkbox"/>	206.020	20 mm	<input type="checkbox"/>	206.050	50 mm
<input type="checkbox"/>	206.022	22 mm	<input type="checkbox"/>	206.055	55 mm
<input type="checkbox"/>	206.024	24 mm	<input type="checkbox"/>	206.060	60 mm
<input type="checkbox"/>	206.026	26 mm			

4.0 mm Cancellous Bone Screws, partially threaded



	Length		Length		
<input type="checkbox"/>	207.010	10 mm	<input type="checkbox"/>	207.026	26 mm
<input type="checkbox"/>	207.012	12 mm	<input type="checkbox"/>	207.028	28 mm
<input type="checkbox"/>	207.014	14 mm	<input type="checkbox"/>	207.030	30 mm
<input type="checkbox"/>	207.016	16 mm	<input type="checkbox"/>	207.035	35 mm
<input type="checkbox"/>	207.018	18 mm	<input type="checkbox"/>	207.040	40 mm
<input type="checkbox"/>	207.020	20 mm	<input type="checkbox"/>	207.045	45 mm
<input type="checkbox"/>	207.022	22 mm	<input type="checkbox"/>	207.050	50 mm
<input type="checkbox"/>	207.024	24 mm			

4.0 mm Cannulated Screws, short thread



	Length		Length		
<input type="checkbox"/>	207.610	10 mm	<input type="checkbox"/>	207.640	40 mm
<input type="checkbox"/>	207.612	12 mm	<input type="checkbox"/>	207.642	42 mm
<input type="checkbox"/>	207.614	14 mm	<input type="checkbox"/>	207.644	44 mm
<input type="checkbox"/>	207.616	16 mm	<input type="checkbox"/>	207.646	46 mm
<input type="checkbox"/>	207.618	18 mm	<input type="checkbox"/>	207.648	48 mm
<input type="checkbox"/>	207.620	20 mm	<input type="checkbox"/>	207.650	50 mm
<input type="checkbox"/>	207.622	22 mm	<input type="checkbox"/>	207.652	52 mm
<input type="checkbox"/>	207.624	24 mm	<input type="checkbox"/>	207.654	54 mm
<input type="checkbox"/>	207.626	26 mm	<input type="checkbox"/>	207.656	56 mm
<input type="checkbox"/>	207.628	28 mm	<input type="checkbox"/>	207.658	58 mm
<input type="checkbox"/>	207.630	30 mm	<input type="checkbox"/>	207.660	60 mm
<input type="checkbox"/>	207.632	32 mm	<input type="checkbox"/>	207.664	64 mm
<input type="checkbox"/>	207.634	34 mm	<input type="checkbox"/>	207.668	68 mm
<input type="checkbox"/>	207.636	36 mm	<input type="checkbox"/>	207.672	72 mm
<input type="checkbox"/>	207.638	38 mm			

4.0 mm Cannulated Screws, long thread



	Length		Length		
<input type="checkbox"/>	207.716	16 mm	<input type="checkbox"/>	207.742	42 mm
<input type="checkbox"/>	207.718	18 mm	<input type="checkbox"/>	207.744	44 mm
<input type="checkbox"/>	207.720	20 mm	<input type="checkbox"/>	207.746	46 mm
<input type="checkbox"/>	207.722	22 mm	<input type="checkbox"/>	207.748	48 mm
<input type="checkbox"/>	207.724	24 mm	<input type="checkbox"/>	207.750	50 mm
<input type="checkbox"/>	207.726	26 mm	<input type="checkbox"/>	207.752	52 mm
<input type="checkbox"/>	207.728	28 mm	<input type="checkbox"/>	207.754	54 mm
<input type="checkbox"/>	207.730	30 mm	<input type="checkbox"/>	207.756	56 mm
<input type="checkbox"/>	207.732	32 mm	<input type="checkbox"/>	207.758	58 mm
<input type="checkbox"/>	207.734	34 mm	<input type="checkbox"/>	207.760	60 mm
<input type="checkbox"/>	207.736	36 mm	<input type="checkbox"/>	207.764	64 mm
<input type="checkbox"/>	207.738	38 mm	<input type="checkbox"/>	207.768	68 mm
<input type="checkbox"/>	207.740	40 mm	<input type="checkbox"/>	207.772	72 mm

3.5 mm LCP® Plates



	Holes	Length		Holes	Length		
<input type="checkbox"/>	223.521	2	33 mm	<input type="checkbox"/>	223.611	11	150 mm
<input type="checkbox"/>	223.531	3	46 mm	<input type="checkbox"/>	223.621	12	163 mm
<input type="checkbox"/>	223.541	4	59 mm	<input type="checkbox"/>	223.631	13	176 mm
<input type="checkbox"/>	223.551	5	72 mm	<input type="checkbox"/>	223.641	14	189 mm
<input type="checkbox"/>	223.561	6	85 mm	<input type="checkbox"/>	223.651	15	202 mm
<input type="checkbox"/>	223.571	7	98 mm	<input type="checkbox"/>	223.661	16	215 mm
<input type="checkbox"/>	223.581	8	111 mm	<input type="checkbox"/>	223.671	18	241 mm
<input type="checkbox"/>	223.591	9	124 mm	<input type="checkbox"/>	223.681	20	267 mm
<input type="checkbox"/>	223.601	10	137 mm	<input type="checkbox"/>	223.691	22	293 mm

3.5 mm LCP T-Plates, right angle,

3 head holes



	Shaft Holes	Length		Shaft Holes	Length		
<input type="checkbox"/>	241.131	3	50 mm	<input type="checkbox"/>	241.162	6	77 mm
<input type="checkbox"/>	241.142	4	57 mm	<input type="checkbox"/>	241.171	7	87 mm
<input type="checkbox"/>	241.151	5	67 mm	<input type="checkbox"/>	241.181	8	97 mm

4 head holes

	Shaft Holes	Length		Shaft Holes	Length		
<input type="checkbox"/>	241.132	3	50 mm	<input type="checkbox"/>	241.161	6	78 mm
<input type="checkbox"/>	241.141	4	56 mm	<input type="checkbox"/>	241.172	7	89 mm
<input type="checkbox"/>	241.152	5	67 mm	<input type="checkbox"/>	241.182	8	100 mm

Inventory Control Form

Small Fragment Locking Compression Plate (LCP) System

Implants (cont'd)

3.5 mm LCP T-Plates, 3 head holes, oblique right



Shaft			Shaft		
	Holes	Length		Holes	Length
<input type="checkbox"/>	241.031	3 52 mm	<input type="checkbox"/>	241.061	6 85 mm
<input type="checkbox"/>	241.041	4 63 mm	<input type="checkbox"/>	241.071	7 96 mm
<input type="checkbox"/>	241.051	5 74 mm	<input type="checkbox"/>	241.081	8 107 mm

oblique left

Shaft			Shaft		
	Holes	Length		Holes	Length
<input type="checkbox"/>	241.931	3 52 mm	<input type="checkbox"/>	241.961	6 85 mm
<input type="checkbox"/>	241.941	4 63 mm	<input type="checkbox"/>	241.971	7 96 mm
<input type="checkbox"/>	241.951	5 74 mm	<input type="checkbox"/>	241.981	8 107 mm

One-Third Tubular LCP Plates, with collar



Holes			Holes		
		Length			Length
<input type="checkbox"/>	241.331	3 33 mm	<input type="checkbox"/>	241.381	8 93 mm
<input type="checkbox"/>	241.341	4 45 mm	<input type="checkbox"/>	241.391	9 105 mm
<input type="checkbox"/>	241.351	5 57 mm	<input type="checkbox"/>	241.401	10 117 mm
<input type="checkbox"/>	241.361	6 69 mm	<input type="checkbox"/>	241.421	12 141 mm
<input type="checkbox"/>	241.371	7 81 mm			

3.5 mm LCP Proximal Humerus Plates, standard



Shaft		
	Holes	Length
<input type="checkbox"/>	241.901	3 90 mm
<input type="checkbox"/>	241.903	5 114 mm

3.5 mm LCP Proximal Humerus Plates, long



Shaft			Shaft		
	Holes	Length		Holes	Length
<input type="checkbox"/>	241.918	5 142 mm	<input type="checkbox"/>	241.923	10 232 mm
<input type="checkbox"/>	241.919	6 160 mm	<input type="checkbox"/>	241.925	12 268 mm
<input type="checkbox"/>	241.921	8 196 mm			

3.5 mm LCP Reconstruction Plates



Shaft			Shaft		
	Holes	Length		Holes	Length
<input type="checkbox"/>	245.041	4 56 mm	<input type="checkbox"/>	245.121	12 168 mm
<input type="checkbox"/>	245.051	5 70 mm	<input type="checkbox"/>	245.131	13 182 mm
<input type="checkbox"/>	245.061	6 84 mm	<input type="checkbox"/>	245.141	14 196 mm
<input type="checkbox"/>	245.071	7 98 mm	<input type="checkbox"/>	245.161	16 224 mm
<input type="checkbox"/>	245.081	8 112 mm	<input type="checkbox"/>	245.181	18 252 mm
<input type="checkbox"/>	245.091	9 126 mm	<input type="checkbox"/>	245.201	20 280 mm
<input type="checkbox"/>	245.101	10 140 mm	<input type="checkbox"/>	245.221	22 308 mm
<input type="checkbox"/>	245.111	11 154 mm			

3.5 mm LCP Curved Reconstruction Plates



Holes			Holes		
		Length			Length
<input type="checkbox"/>	245.341	4	<input type="checkbox"/>	245.421	12
<input type="checkbox"/>	245.361	6	<input type="checkbox"/>	245.441	14
<input type="checkbox"/>	245.381	8	<input type="checkbox"/>	245.461	16
<input type="checkbox"/>	245.401	10	<input type="checkbox"/>	245.481	18

3.5 mm LCP Metaphyseal Plates



Holes			Holes		
		Length			Length
<input type="checkbox"/>	223.406	6 86 mm	<input type="checkbox"/>	223.411	11 151 mm
<input type="checkbox"/>	223.407	7 99 mm	<input type="checkbox"/>	223.412	12 164 mm
<input type="checkbox"/>	223.408	8 112 mm	<input type="checkbox"/>	223.414	14 190 mm
<input type="checkbox"/>	223.409	9 125 mm	<input type="checkbox"/>	223.416	16 216 mm
<input type="checkbox"/>	223.410	10 138 mm	<input type="checkbox"/>	223.418	18 242 mm

Miscellaneous Implants

<input type="checkbox"/>	219.98	Washer, 7 mm
<input type="checkbox"/>	219.931	Spiked Washer, 8.0 mm/3.2 mm
<input type="checkbox"/>	219.941	Spiked Washer, 13.5 mm/4.0 mm
<input type="checkbox"/>	292.12	1.25 mm Kirschner Wire, 150 mm, 10 pack
<input type="checkbox"/>	292.71	1.6 mm Kirschner Wire with 5 mm thread, 150 mm, 10 pack
<input type="checkbox"/>	292.20	2.0 mm Kirschner Wire, 150 mm, 10 pack

Inventory Control Form

Small Fragment Locking Compression Plate (LCP) System

Instruments

Drill Bits, quick coupling

		Diameter	Length	
<input type="checkbox"/>	310.21	2.0 mm	125 mm	
<input type="checkbox"/>	310.23	2.5 mm	180 mm, gold	
<input type="checkbox"/>	310.25	2.5 mm	110 mm, gold	
<input type="checkbox"/>	315.28	2.7 mm	125 mm	
<input type="checkbox"/>	310.288	2.8 mm	165 mm	
<input type="checkbox"/>	03.213.002	3.1 mm	165 mm	
<input type="checkbox"/>	310.35	3.5 mm	110 mm	
		Diameter	Length	Calibration
<input type="checkbox"/>	03.122.002	2.8 mm	248 mm	95 mm
<input type="checkbox"/>	324.214	2.8 mm	200 mm	100 mm

Taps

<input type="checkbox"/>	311.32	For 3.5 mm Cortex Screws
<input type="checkbox"/>	311.34	For 4.0 mm Cancellous Bone Screws

Bending Templates

		Holes
<input type="checkbox"/>	329.820	12
<input type="checkbox"/>	329.87	7
<input type="checkbox"/>	329.89	9

Other



324.024 Push-Pull Reduction Device

Instruments for 4.0 mm Cannulated Screws

<input type="checkbox"/>	310.67	2.7 mm Cannulated Drill Bit, quick coupling, 160 mm
<input type="checkbox"/>	311.63	Cannulated Tap for 4.0 mm Cannulated Screws, 147 mm
<input type="checkbox"/>	900.722	1.25 mm Threaded Guide Wire, 150 mm
<input type="checkbox"/>	900.721	1.25 mm Non-Threaded Guide Wire, 150 mm

Some devices in this form may not have been licensed in accordance with Canadian law and may not be for sale in Canada. Please contact your sales consultant for items approved for sale in Canada.



Manufactured or distributed by:

Synthes USA Products, LLC
1302 Wrights Lane East
West Chester, PA 19380

Synthes USA, LLC
1101 Synthes Avenue
Monument, CO 80132

To order (USA): 800-523-0322
To order (Canada): 855-946-8999

Note: For recognized manufacturer, refer to the product label.

www.depuyssynthes.com