

Inventory Control Form

Locking Periarticular Plating System

Case Information (eg, Case ID):

DO NOT PUT ANY
PATIENT IDENTIFIABLE
INFORMATION IN
THIS FIELD

To order (USA): 800-523-0322

To order (Canada): 855-946-8999

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

4.0 mm Locking Screws, self-tapping, with T25 StarDrive™ Recess



	Length		Length
<input type="checkbox"/>	02.204.014 14 mm	<input type="checkbox"/>	02.204.040 40 mm
<input type="checkbox"/>	02.204.016 16 mm	<input type="checkbox"/>	02.204.042 42 mm
<input type="checkbox"/>	02.204.018 18 mm	<input type="checkbox"/>	02.204.044 44 mm
<input type="checkbox"/>	02.204.020 20 mm	<input type="checkbox"/>	02.204.046 46 mm
<input type="checkbox"/>	02.204.022 22 mm	<input type="checkbox"/>	02.204.048 48 mm
<input type="checkbox"/>	02.204.024 24 mm	<input type="checkbox"/>	02.204.050 50 mm
<input type="checkbox"/>	02.204.026 26 mm	<input type="checkbox"/>	02.204.052 52 mm
<input type="checkbox"/>	02.204.028 28 mm	<input type="checkbox"/>	02.204.054 54 mm
<input type="checkbox"/>	02.204.030 30 mm	<input type="checkbox"/>	02.204.056 56 mm
<input type="checkbox"/>	02.204.032 32 mm	<input type="checkbox"/>	02.204.058 58 mm
<input type="checkbox"/>	02.204.034 34 mm	<input type="checkbox"/>	02.204.060 60 mm
<input type="checkbox"/>	02.204.036 36 mm	<input type="checkbox"/>	02.204.062 62 mm
<input type="checkbox"/>	02.204.038 38 mm		

5.0 mm Cannulated Conical Screws



	Length		Length
<input type="checkbox"/>	02.205.240 40 mm	<input type="checkbox"/>	02.205.270 70 mm
<input type="checkbox"/>	02.205.245 45 mm	<input type="checkbox"/>	02.205.275 75 mm
<input type="checkbox"/>	02.205.250 50 mm	<input type="checkbox"/>	02.205.280 80 mm
<input type="checkbox"/>	02.205.255 55 mm	<input type="checkbox"/>	02.205.285 85 mm
<input type="checkbox"/>	02.205.260 60 mm	<input type="checkbox"/>	02.205.290 90 mm
<input type="checkbox"/>	02.205.265 65 mm	<input type="checkbox"/>	02.205.295 95 mm

5.0 mm Screw Nut

222.578



4.5 mm Cortex Screws, self-tapping



	Length		Length
<input type="checkbox"/>	214.814 14 mm	<input type="checkbox"/>	214.846 46 mm
<input type="checkbox"/>	214.816 16 mm	<input type="checkbox"/>	214.848 48 mm
<input type="checkbox"/>	214.818 18 mm	<input type="checkbox"/>	214.850 50 mm
<input type="checkbox"/>	214.820 20 mm	<input type="checkbox"/>	214.852 52 mm
<input type="checkbox"/>	214.822 22 mm	<input type="checkbox"/>	214.854 54 mm
<input type="checkbox"/>	214.824 24 mm	<input type="checkbox"/>	214.856 56 mm
<input type="checkbox"/>	214.826 26 mm	<input type="checkbox"/>	214.858 58 mm
<input type="checkbox"/>	214.828 28 mm	<input type="checkbox"/>	214.860 60 mm
<input type="checkbox"/>	214.830 30 mm	<input type="checkbox"/>	214.862 62 mm
<input type="checkbox"/>	214.832 32 mm	<input type="checkbox"/>	214.864 64 mm
<input type="checkbox"/>	214.834 34 mm	<input type="checkbox"/>	214.866 66 mm
<input type="checkbox"/>	214.836 36 mm	<input type="checkbox"/>	214.868 68 mm
<input type="checkbox"/>	214.838 38 mm	<input type="checkbox"/>	214.870 70 mm
<input type="checkbox"/>	214.840 40 mm		
<input type="checkbox"/>	214.842 42 mm		
<input type="checkbox"/>	214.844 44 mm		

5.0 mm Cannulated Locking Screws



	Length		Length
<input type="checkbox"/>	02.205.025 25 mm	<input type="checkbox"/>	02.205.100 100 mm
<input type="checkbox"/>	02.205.030 30 mm	<input type="checkbox"/>	02.205.105 105 mm
<input type="checkbox"/>	02.205.035 35 mm	<input type="checkbox"/>	02.205.110 110 mm
<input type="checkbox"/>	02.205.040 40 mm	<input type="checkbox"/>	02.205.115 115 mm
<input type="checkbox"/>	02.205.045 45 mm	<input type="checkbox"/>	02.205.120 120 mm
<input type="checkbox"/>	02.205.050 50 mm	<input type="checkbox"/>	02.205.125 125 mm
<input type="checkbox"/>	02.205.055 55 mm	<input type="checkbox"/>	02.205.130 130 mm
<input type="checkbox"/>	02.205.060 60 mm	<input type="checkbox"/>	02.205.135 135 mm
<input type="checkbox"/>	02.205.065 65 mm	<input type="checkbox"/>	02.205.140 140 mm
<input type="checkbox"/>	02.205.070 70 mm	<input type="checkbox"/>	02.205.145 145 mm
<input type="checkbox"/>	02.205.075 75 mm		
<input type="checkbox"/>	02.205.080 80 mm		
<input type="checkbox"/>	02.205.085 85 mm		
<input type="checkbox"/>	02.205.090 90 mm		
<input type="checkbox"/>	02.205.095 95 mm		

Locking Periarticular Plating System

Implants (cont'd)

5.0 mm Locking Screws, self-tapping, with T25 StarDrive Recess



	Length		Length
<input type="checkbox"/>	14 mm	<input type="checkbox"/>	42 mm
<input type="checkbox"/>	16 mm	<input type="checkbox"/>	44 mm
<input type="checkbox"/>	18 mm	<input type="checkbox"/>	46 mm
<input type="checkbox"/>	20 mm	<input type="checkbox"/>	48 mm
<input type="checkbox"/>	22 mm	<input type="checkbox"/>	50 mm
<input type="checkbox"/>	24 mm	<input type="checkbox"/>	55 mm
<input type="checkbox"/>	26 mm	<input type="checkbox"/>	60 mm
<input type="checkbox"/>	28 mm	<input type="checkbox"/>	65 mm
<input type="checkbox"/>	30 mm	<input type="checkbox"/>	70 mm
<input type="checkbox"/>	32 mm	<input type="checkbox"/>	75 mm
<input type="checkbox"/>	34 mm	<input type="checkbox"/>	80 mm
<input type="checkbox"/>	36 mm	<input type="checkbox"/>	85 mm
<input type="checkbox"/>	38 mm	<input type="checkbox"/>	90 mm
<input type="checkbox"/>	40 mm		

5.0 mm Periprosthetic Locking Screws, self-tapping[◇]



	Length		Length
<input type="checkbox"/>	8 mm	<input type="checkbox"/>	14 mm
<input type="checkbox"/>	10 mm	<input type="checkbox"/>	18 mm
<input type="checkbox"/>	12 mm		

6.5 mm Cancellous Bone Screws, 16 mm thread



	Length		Length
<input type="checkbox"/>	50 mm	<input type="checkbox"/>	75 mm
<input type="checkbox"/>	55 mm	<input type="checkbox"/>	80 mm
<input type="checkbox"/>	60 mm	<input type="checkbox"/>	85 mm
<input type="checkbox"/>	65 mm	<input type="checkbox"/>	90 mm
<input type="checkbox"/>	70 mm	<input type="checkbox"/>	95 mm

6.5 mm Cancellous Bone Screws, 32 mm thread



	Length		Length
<input type="checkbox"/>	50 mm	<input type="checkbox"/>	75 mm
<input type="checkbox"/>	55 mm	<input type="checkbox"/>	80 mm
<input type="checkbox"/>	60 mm	<input type="checkbox"/>	85 mm
<input type="checkbox"/>	65 mm	<input type="checkbox"/>	90 mm
<input type="checkbox"/>	70 mm	<input type="checkbox"/>	95 mm

6.5 mm Cancellous Bone Screws, fully threaded



	Length		Length
<input type="checkbox"/>	50 mm	<input type="checkbox"/>	75 mm
<input type="checkbox"/>	55 mm	<input type="checkbox"/>	80 mm
<input type="checkbox"/>	60 mm	<input type="checkbox"/>	85 mm
<input type="checkbox"/>	65 mm	<input type="checkbox"/>	90 mm
<input type="checkbox"/>	70 mm	<input type="checkbox"/>	95 mm

7.3 mm Cannulated Conical Screws, fully threaded



	Length		Length
<input type="checkbox"/>	50 mm	<input type="checkbox"/>	75 mm
<input type="checkbox"/>	55 mm	<input type="checkbox"/>	80 mm
<input type="checkbox"/>	60 mm	<input type="checkbox"/>	85 mm
<input type="checkbox"/>	65 mm	<input type="checkbox"/>	90 mm
<input type="checkbox"/>	70 mm	<input type="checkbox"/>	95 mm

7.3 mm Cannulated Locking Screws



	Length		Length
<input type="checkbox"/>	20 mm	<input type="checkbox"/>	85 mm
<input type="checkbox"/>	25 mm	<input type="checkbox"/>	90 mm
<input type="checkbox"/>	30 mm	<input type="checkbox"/>	95 mm
<input type="checkbox"/>	35 mm	<input type="checkbox"/>	100 mm
<input type="checkbox"/>	40 mm	<input type="checkbox"/>	105 mm
<input type="checkbox"/>	45 mm	<input type="checkbox"/>	110 mm
<input type="checkbox"/>	50 mm	<input type="checkbox"/>	115 mm
<input type="checkbox"/>	55 mm	<input type="checkbox"/>	120 mm
<input type="checkbox"/>	60 mm	<input type="checkbox"/>	125 mm
<input type="checkbox"/>	65 mm	<input type="checkbox"/>	130 mm
<input type="checkbox"/>	70 mm	<input type="checkbox"/>	135 mm
<input type="checkbox"/>	75 mm	<input type="checkbox"/>	140 mm
<input type="checkbox"/>	80 mm	<input type="checkbox"/>	145 mm

[◇]Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.

Locking Periarticular Plating System

Implants (cont'd)

7.3 mm Cannulated Conical Screws, partially threaded



	Length		Length		
<input type="checkbox"/>	02.207.450	50 mm	<input type="checkbox"/>	02.207.500	100 mm
<input type="checkbox"/>	02.207.455	55 mm	<input type="checkbox"/>	02.207.505	105 mm
<input type="checkbox"/>	02.207.460	60 mm	<input type="checkbox"/>	02.207.510	110 mm
<input type="checkbox"/>	02.207.465	65 mm	<input type="checkbox"/>	02.207.515	115 mm
<input type="checkbox"/>	02.207.470	70 mm	<input type="checkbox"/>	02.207.520	120 mm
<input type="checkbox"/>	02.207.475	75 mm	<input type="checkbox"/>	02.207.525	125 mm
<input type="checkbox"/>	02.207.480	80 mm	<input type="checkbox"/>	02.207.530	130 mm
<input type="checkbox"/>	02.207.485	85 mm	<input type="checkbox"/>	02.207.535	135 mm
<input type="checkbox"/>	02.207.490	90 mm	<input type="checkbox"/>	02.207.540	140 mm
<input type="checkbox"/>	02.207.495	95 mm	<input type="checkbox"/>	02.207.545	145 mm

4.5 mm LCP® Condylar Plates



	Holes	Length	
<input type="checkbox"/>	222.656	6	170 mm right
<input type="checkbox"/>	222.657	6	170 mm left
<input type="checkbox"/>	222.658	8	206 mm right
<input type="checkbox"/>	222.659	8	206 mm left
<input type="checkbox"/>	222.660	10	242 mm right
<input type="checkbox"/>	222.661	10	242 mm left
<input type="checkbox"/>	222.662	12	278 mm right
<input type="checkbox"/>	222.663	12	278 mm left
<input type="checkbox"/>	222.664	14	314 mm right
<input type="checkbox"/>	222.665	14	314 mm left
<input type="checkbox"/>	222.666	16	350 mm right
<input type="checkbox"/>	222.667	16	350 mm left
<input type="checkbox"/>	222.668	18	386 mm right
<input type="checkbox"/>	222.669	18	386 mm left

4.5 mm LCP Curved Condylar Plates



	Holes	Length		
<input type="checkbox"/>	02.001.300	10	242 mm	left
<input type="checkbox"/>	02.001.320	10	242 mm	right
<input type="checkbox"/>	02.001.302	12	278 mm	left
<input type="checkbox"/>	02.001.322	12	278 mm	right
<input type="checkbox"/>	02.001.304	14	314 mm	left
<input type="checkbox"/>	02.001.324	14	314 mm	right
<input type="checkbox"/>	02.001.306	16	350 mm	left
<input type="checkbox"/>	02.001.326	16	350 mm	right
<input type="checkbox"/>	02.001.308	18	386 mm	left
<input type="checkbox"/>	02.001.328	18	386 mm	right
<input type="checkbox"/>	02.001.310S	20	422 mm	left (sterile only)
<input type="checkbox"/>	02.001.330S	20	422 mm	right (sterile only)
<input type="checkbox"/>	02.001.312S	22	458 mm	left (sterile only)
<input type="checkbox"/>	02.001.332S	22	458 mm	right (sterile only)

4.5 mm LCP Medial Proximal Tibia Plates



	Holes	Length	
<input type="checkbox"/>	239.984	4	106 mm right
<input type="checkbox"/>	239.985	4	106 mm left
<input type="checkbox"/>	239.986	6	142 mm right
<input type="checkbox"/>	239.987	6	142 mm left
<input type="checkbox"/>	239.988	8	178 mm right
<input type="checkbox"/>	239.989	8	178 mm left
<input type="checkbox"/>	239.990	10	214 mm right
<input type="checkbox"/>	239.991	10	214 mm left
<input type="checkbox"/>	239.992	12	250 mm right
<input type="checkbox"/>	239.993	12	250 mm left
<input type="checkbox"/>	239.994	14	286 mm right
<input type="checkbox"/>	239.995	14	286 mm left
<input type="checkbox"/>	239.996	16	322 mm right
<input type="checkbox"/>	239.997	16	322 mm left

4.5 mm LCP Proximal Tibia Plates



	Holes	Length	
<input type="checkbox"/>	240.036	4	82 mm right
<input type="checkbox"/>	240.037	4	82 mm left
<input type="checkbox"/>	240.038	6	118 mm right
<input type="checkbox"/>	240.039	6	118 mm left
<input type="checkbox"/>	240.040	8	154 mm right
<input type="checkbox"/>	240.041	8	154 mm left
<input type="checkbox"/>	240.042	10	190 mm right
<input type="checkbox"/>	240.043	10	190 mm left
<input type="checkbox"/>	240.044	12	226 mm right
<input type="checkbox"/>	240.045	12	226 mm left
<input type="checkbox"/>	240.046	14	262 mm right
<input type="checkbox"/>	240.047	14	262 mm left
<input type="checkbox"/>	240.048S	16	298 mm right, (sterile only)
<input type="checkbox"/>	240.049S	16	298 mm left, (sterile only)
<input type="checkbox"/>	240.052S	18	334 mm right, (sterile only)
<input type="checkbox"/>	240.053S	18	334 mm left, (sterile only)
<input type="checkbox"/>	240.054S	20	370 mm right, (sterile only)
<input type="checkbox"/>	240.055S	20	370 mm left, (sterile only)

◇Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.

Inventory Control Form

Locking Periarticular Plating System

Implants (cont'd)

4.5 mm LCP Proximal Femur Plates [◇]



	Holes	Length	
<input type="checkbox"/> 242.102	2	139 mm	left
<input type="checkbox"/> 242.802	2	139 mm	right
<input type="checkbox"/> 242.104	4	175 mm	left
<input type="checkbox"/> 242.804	4	175 mm	right
<input type="checkbox"/> 242.106	6	211 mm	left
<input type="checkbox"/> 242.806	6	211 mm	right
<input type="checkbox"/> 242.108	8	247 mm	left
<input type="checkbox"/> 242.808	8	247 mm	right
<input type="checkbox"/> 242.110	10	283 mm	left
<input type="checkbox"/> 242.810	10	283 mm	right
<input type="checkbox"/> 242.112	12	319 mm	left
<input type="checkbox"/> 242.812	12	319 mm	right
<input type="checkbox"/> 242.114	14	355 mm	left
<input type="checkbox"/> 242.814	14	355 mm	right
<input type="checkbox"/> 242.116	16	391 mm	left
<input type="checkbox"/> 242.816	16	391 mm	right



4.5 mm LCP Proximal Femur Hook Plates [◇]

	Holes	Length
<input type="checkbox"/> 242.120	2	133 mm
<input type="checkbox"/> 242.121	4	169 mm
<input type="checkbox"/> 242.122	6	205 mm
<input type="checkbox"/> 242.123	8	241 mm
<input type="checkbox"/> 242.124	10	277 mm
<input type="checkbox"/> 242.125	12	313 mm
<input type="checkbox"/> 242.126	14	349 mm
<input type="checkbox"/> 242.127	16	385 mm
<input type="checkbox"/> 242.128	18	421 mm



Instruments

Guide Wires

<input type="checkbox"/> 292.652	2.0 mm Non-Colored Threaded Guide Wire, spade point, 230 mm
<input type="checkbox"/> 310.243	2.5 mm Drill Tip Guide Wire, 200 mm
<input type="checkbox"/> 338.002	2.5 mm Drill Tip Guide Wire with 12 mm thread, 300 mm
<input type="checkbox"/> 03.120.026	2.5 mm Drill Tip Guide Wire, non-threaded, 300 mm

Drill Bits

<input type="checkbox"/> 310.31 [◇]	3.2 mm Drill Bit, quick coupling, 145 mm
<input type="checkbox"/> 310.431	4.3 mm Drill Bit, quick coupling, for 5.0 mm Locking Screws, 180 mm
<input type="checkbox"/> 310.44 [◇]	4.5 mm Drill Bit, quick coupling, 145 mm
<input type="checkbox"/> 310.632	5.0 mm Cannulated Drill Bit, quick coupling, 200 mm
<input type="checkbox"/> 310.634	4.3 mm Cannulated Drill Bit, quick coupling, 200 mm
<input type="checkbox"/> 324.212	3.2 mm Percutaneous Drill Bit, quick coupling, 300 mm, calibrated

Taps

<input type="checkbox"/> 311.46	Tap for 4.5 mm Cortex/Shaft Screws
<input type="checkbox"/> 311.66	Tap for 6.5 mm Cancellous Bone Screws

Reduction Devices

<input type="checkbox"/> 03.120.023	Pull Reduction Device, for 4.3 mm Percutaneous Drill Guide (includes nut 03.120.024)
<input type="checkbox"/> 311.449	Push-Pull Reduction Device, for use with 4.5 mm LCP plates

[◇]Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.

Some devices in this form may not have been licensed in accordance with Canadian law and may not be for sale in Canada. Please contact your sales consultant for items approved for sale in Canada.



PART OF THE **Johnson & Johnson** FAMILY OF COMPANIES

Manufactured or distributed by:

Synthes USA Products, LLC
1302 Wrights Lane East
West Chester, PA 19380

Synthes USA, LLC
1101 Synthes Avenue
Monument, CO 80132

To order (USA): 800-523-0322

To order (Canada): 855-946-8999

Note: For recognized manufacturer, refer to the product label.

www.depuysynthes.com