

# Inventory Control Form

## Hindfoot Arthrodesis Nail-EX System



Patient Information:

Synthes (USA)  
To Order: (800) 523-0322

Synthes (Canada) Ltd.  
To Order: (800) 668-1119

Date: \_\_\_\_\_

Hospital: \_\_\_\_\_

Surgeon: \_\_\_\_\_

Procedure: \_\_\_\_\_

### Screws

#### 5.0 mm Titanium Locking Screws, with T25 StarDrive recess, for IM Nails<sup>◇</sup>



|                          |            | LENGTH |                          |            | LENGTH |
|--------------------------|------------|--------|--------------------------|------------|--------|
| <input type="checkbox"/> | 04.005.516 | 26 mm  | <input type="checkbox"/> | 04.005.548 | 58 mm  |
| <input type="checkbox"/> | 04.005.518 | 28 mm  | <input type="checkbox"/> | 04.005.550 | 60 mm  |
| <input type="checkbox"/> | 04.005.520 | 30 mm  | <input type="checkbox"/> | 04.005.552 | 62 mm  |
| <input type="checkbox"/> | 04.005.522 | 32 mm  | <input type="checkbox"/> | 04.005.554 | 64 mm  |
| <input type="checkbox"/> | 04.005.524 | 34 mm  | <input type="checkbox"/> | 04.005.556 | 66 mm  |
| <input type="checkbox"/> | 04.005.526 | 36 mm  | <input type="checkbox"/> | 04.005.558 | 68 mm  |
| <input type="checkbox"/> | 04.005.528 | 38 mm  | <input type="checkbox"/> | 04.005.560 | 70 mm  |
| <input type="checkbox"/> | 04.005.530 | 40 mm  | <input type="checkbox"/> | 04.005.562 | 72 mm  |
| <input type="checkbox"/> | 04.005.532 | 42 mm  | <input type="checkbox"/> | 04.005.564 | 74 mm  |
| <input type="checkbox"/> | 04.005.534 | 44 mm  | <input type="checkbox"/> | 04.005.566 | 76 mm  |
| <input type="checkbox"/> | 04.005.536 | 46 mm  | <input type="checkbox"/> | 04.005.568 | 78 mm  |
| <input type="checkbox"/> | 04.005.538 | 48 mm  | <input type="checkbox"/> | 04.005.570 | 80 mm  |
| <input type="checkbox"/> | 04.005.540 | 50 mm  | <input type="checkbox"/> | 04.005.575 | 85 mm  |
| <input type="checkbox"/> | 04.005.542 | 52 mm  | <input type="checkbox"/> | 04.005.580 | 90 mm  |
| <input type="checkbox"/> | 04.005.544 | 54 mm  | <input type="checkbox"/> | 04.005.585 | 95 mm  |
| <input type="checkbox"/> | 04.005.546 | 56 mm  | <input type="checkbox"/> | 04.005.590 | 100 mm |

#### 6.0 mm Titanium Locking Screws, with T25 StarDrive recess, for IM Nails<sup>◇</sup>



|                          |            | LENGTH |                          |            | LENGTH |
|--------------------------|------------|--------|--------------------------|------------|--------|
| <input type="checkbox"/> | 04.005.616 | 26 mm  | <input type="checkbox"/> | 04.005.648 | 58 mm  |
| <input type="checkbox"/> | 04.005.618 | 28 mm  | <input type="checkbox"/> | 04.005.650 | 60 mm  |
| <input type="checkbox"/> | 04.005.620 | 30 mm  | <input type="checkbox"/> | 04.005.654 | 64 mm  |
| <input type="checkbox"/> | 04.005.622 | 32 mm  | <input type="checkbox"/> | 04.005.658 | 68 mm  |
| <input type="checkbox"/> | 04.005.624 | 34 mm  | <input type="checkbox"/> | 04.005.662 | 72 mm  |
| <input type="checkbox"/> | 04.005.626 | 36 mm  | <input type="checkbox"/> | 04.005.666 | 76 mm  |
| <input type="checkbox"/> | 04.005.628 | 38 mm  | <input type="checkbox"/> | 04.005.670 | 80 mm  |
| <input type="checkbox"/> | 04.005.630 | 40 mm  | <input type="checkbox"/> | 04.005.675 | 85 mm  |
| <input type="checkbox"/> | 04.005.632 | 42 mm  | <input type="checkbox"/> | 04.005.680 | 90 mm  |
| <input type="checkbox"/> | 04.005.634 | 44 mm  | <input type="checkbox"/> | 04.005.685 | 95 mm  |
| <input type="checkbox"/> | 04.005.636 | 46 mm  | <input type="checkbox"/> | 04.005.690 | 100 mm |
| <input type="checkbox"/> | 04.005.638 | 48 mm  | <input type="checkbox"/> | 04.005.691 | 105 mm |
| <input type="checkbox"/> | 04.005.640 | 50 mm  | <input type="checkbox"/> | 04.005.692 | 110 mm |
| <input type="checkbox"/> | 04.005.642 | 52 mm  | <input type="checkbox"/> | 04.005.693 | 115 mm |
| <input type="checkbox"/> | 04.005.644 | 54 mm  | <input type="checkbox"/> | 04.005.694 | 120 mm |
| <input type="checkbox"/> | 04.005.646 | 56 mm  | <input type="checkbox"/> | 04.005.695 | 125 mm |

#### 5.0 mm Titanium Locking Screws, with hexagonal recess



|                          |         | LENGTH |                          |         | LENGTH |
|--------------------------|---------|--------|--------------------------|---------|--------|
| <input type="checkbox"/> | 458.926 | 26 mm  | <input type="checkbox"/> | 458.954 | 54 mm  |
| <input type="checkbox"/> | 458.928 | 28 mm  | <input type="checkbox"/> | 458.956 | 56 mm  |
| <input type="checkbox"/> | 458.930 | 30 mm  | <input type="checkbox"/> | 458.958 | 58 mm  |
| <input type="checkbox"/> | 458.932 | 32 mm  | <input type="checkbox"/> | 458.960 | 60 mm  |
| <input type="checkbox"/> | 458.934 | 34 mm  | <input type="checkbox"/> | 458.964 | 64 mm  |
| <input type="checkbox"/> | 458.936 | 36 mm  | <input type="checkbox"/> | 458.968 | 68 mm  |
| <input type="checkbox"/> | 458.938 | 38 mm  | <input type="checkbox"/> | 458.972 | 72 mm  |
| <input type="checkbox"/> | 458.940 | 40 mm  | <input type="checkbox"/> | 458.976 | 76 mm  |
| <input type="checkbox"/> | 458.942 | 42 mm  | <input type="checkbox"/> | 458.980 | 80 mm  |
| <input type="checkbox"/> | 458.944 | 44 mm  | <input type="checkbox"/> | 458.985 | 85 mm  |
| <input type="checkbox"/> | 458.946 | 46 mm  | <input type="checkbox"/> | 458.990 | 90 mm  |
| <input type="checkbox"/> | 458.948 | 48 mm  | <input type="checkbox"/> | 458.995 | 95 mm  |
| <input type="checkbox"/> | 458.950 | 50 mm  | <input type="checkbox"/> | 458.999 | 100 mm |
| <input type="checkbox"/> | 458.952 | 52 mm  |                          |         |        |

#### 6.0 mm Titanium Locking Screws, with hexagonal recess



|                          |         | LENGTH |                          |         | LENGTH |
|--------------------------|---------|--------|--------------------------|---------|--------|
| <input type="checkbox"/> | 450.873 | 30 mm  | <input type="checkbox"/> | 450.866 | 70 mm  |
| <input type="checkbox"/> | 450.874 | 35 mm  | <input type="checkbox"/> | 450.867 | 75 mm  |
| <input type="checkbox"/> | 450.875 | 40 mm  | <input type="checkbox"/> | 450.868 | 80 mm  |
| <input type="checkbox"/> | 450.861 | 45 mm  | <input type="checkbox"/> | 450.869 | 85 mm  |
| <input type="checkbox"/> | 450.862 | 50 mm  | <input type="checkbox"/> | 450.870 | 90 mm  |
| <input type="checkbox"/> | 450.863 | 55 mm  | <input type="checkbox"/> | 450.871 | 95 mm  |
| <input type="checkbox"/> | 450.864 | 60 mm  | <input type="checkbox"/> | 450.872 | 100 mm |
| <input type="checkbox"/> | 450.865 | 65 mm  |                          |         |        |

<sup>◇</sup> Available nonsterile or sterile-packed. Add "S" to catalog number for sterile product.

## Implants

### 10 mm Titanium Hindfoot Arthrodesis Cannulated Nails-EX, sterile

|                          |             | EXTENSION     |
|--------------------------|-------------|---------------|
| <input type="checkbox"/> | 04.008.010S | 150 mm, right |
| <input type="checkbox"/> | 04.008.016S | 180 mm, right |
| <input type="checkbox"/> | 04.008.028S | 240 mm, right |
| <input type="checkbox"/> | 04.008.060S | 150 mm, left  |
| <input type="checkbox"/> | 04.008.066S | 180 mm, left  |
| <input type="checkbox"/> | 04.008.078S | 240 mm, left  |



### 12 mm Titanium Hindfoot Arthrodesis Cannulated Nails-EX, sterile

|                          |             | EXTENSION     |
|--------------------------|-------------|---------------|
| <input type="checkbox"/> | 04.008.210S | 150 mm, right |
| <input type="checkbox"/> | 04.008.216S | 180 mm, right |
| <input type="checkbox"/> | 04.008.228S | 240 mm, right |
| <input type="checkbox"/> | 04.008.260S | 150 mm, left  |
| <input type="checkbox"/> | 04.008.266S | 180 mm, left  |
| <input type="checkbox"/> | 04.008.278S | 240 mm, left  |

### 13 mm Titanium Hindfoot Arthrodesis Cannulated Nails-EX, sterile

|                          |             | EXTENSION     |
|--------------------------|-------------|---------------|
| <input type="checkbox"/> | 04.008.310S | 150 mm, right |
| <input type="checkbox"/> | 04.008.316S | 180 mm, right |
| <input type="checkbox"/> | 04.008.328S | 240 mm, right |
| <input type="checkbox"/> | 04.008.360S | 150 mm, left  |
| <input type="checkbox"/> | 04.008.366S | 180 mm, left  |
| <input type="checkbox"/> | 04.008.378S | 240 mm, left  |

### Titanium Spiral Blades, for Titanium Retrograde Femoral Nails-EX<sup>◇</sup>

|                          |            | LENGTH |                          |            | LENGTH |
|--------------------------|------------|--------|--------------------------|------------|--------|
| <input type="checkbox"/> | 04.013.041 | 45 mm  | <input type="checkbox"/> | 04.013.047 | 75 mm  |
| <input type="checkbox"/> | 04.013.042 | 50 mm  | <input type="checkbox"/> | 04.013.048 | 80 mm  |
| <input type="checkbox"/> | 04.013.043 | 55 mm  | <input type="checkbox"/> | 04.013.049 | 85 mm  |
| <input type="checkbox"/> | 04.013.044 | 60 mm  | <input type="checkbox"/> | 04.013.050 | 90 mm  |
| <input type="checkbox"/> | 04.013.045 | 65 mm  | <input type="checkbox"/> | 04.013.051 | 95 mm  |
| <input type="checkbox"/> | 04.013.046 | 70 mm  | <input type="checkbox"/> | 04.013.052 | 100 mm |



### Titanium End Cap T25 StarDrive for Hindfoot Arthrodesis Nails-EX<sup>◇</sup>

|                          |            | EXTENSION |
|--------------------------|------------|-----------|
| <input type="checkbox"/> | 04.008.001 | 0 mm      |



### Titanium End Cap T25 StarDrive for Hindfoot Arthrodesis Nails-EX Spiral Blade<sup>◇</sup>

|                          |            |
|--------------------------|------------|
| <input type="checkbox"/> | 04.008.000 |
|--------------------------|------------|



## Instruments

### Guide Wire

|                          |            |                           |
|--------------------------|------------|---------------------------|
| <input type="checkbox"/> | 03.010.115 | 3.2 mm Guide Wire, 290 mm |
| <input type="checkbox"/> | 357.399    | 3.2 mm Guide Wire, 400 mm |

### Drill Bits<sup>◇</sup>

|                          |            |   |
|--------------------------|------------|---|
| <input type="checkbox"/> | 351.27     | 13.0 mm Cannulated Drill Bit, 300 mm <sup>◇</sup>                         |
| <input type="checkbox"/> | 03.008.008 | 5.0 mm Three-Fluted Drill Bit, quick coupling, 356 mm, 126 mm calibration |
| <input type="checkbox"/> | 03.010.061 | 4.2 mm Three-Fluted Drill Bit, quick coupling, 330 mm, 100 mm calibration |



### Reaming Rods

|                          |          |   |
|--------------------------|----------|---|
| <input type="checkbox"/> | 351.706S | 2.5 mm Reaming Rod with ball tip, 950 mm, sterile |
|--------------------------|----------|---|



|                          |          |   |
|--------------------------|----------|---|
| <input type="checkbox"/> | 351.707S | 2.5 mm Reaming Rod with ball tip and extension, 950 mm, sterile |
|--------------------------|----------|---|



|                          |                     |   |
|--------------------------|---------------------|---|
| <input type="checkbox"/> | 351.71 <sup>◇</sup> | 3.0 mm Reaming Rod with offset ball tip, 950 mm   |
| <input type="checkbox"/> | 351.76 <sup>◇</sup> | 3.0 mm Reaming Rod with straight ball tip, 950 mm |

